



UX-46 TRU-TEST SUPREME HIQ POLYURETHANE ENAMEL

MSDS Number

BMMTK

National Stock Number

8010-00F021865

Product Name

UX-46 TRU-TEST SUPREME HIQ POLYURETHANE ENAMEL

Manufacturer

TRU TEST MANUFACTURING COMPANY

Product Identification

Product ID:UX-46 TRU-TEST SUPREME HIQ POLYURETHANE ENAMEL

MSDS Date:07/25/1990

FSC:8010

NIIN:00F021865

MSDS Number: BMMTK

Responsible Party

TRU-TEST MANUFACTURING COMPANY

201 JANDUS ROAD

CARY , IL 60013

Emergency Phone: 1-800-228-5635

Info Phone: 1-800-639-5383

Cage: TRUTE

Contractor

TRU-TEST MANUFACTURING CO

CARY, IL 60013

US

708-639-5383

Cage: TRUTE

Ingredients

KEROSENE (PETROLEUM), HYDROTREATED; PETROLEUM DISTILLATE,

CAS: 64742-47-8

RTECS: OA5504000

Fraction By Weight: 34-45%

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:EYES: IRRITATION. SKIN: DRYING.

INHALATION: HEADACHE, DIZZINESS & NAUSEA.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:EYES: IRRITATION. SKIN: DRYING. INHALATION:

HEADACHE, DIZZINESS & NAUSEA.

First Aid

First Aid:EYES: WASH W/FRESH WATER. SKIN: WASH W/WARM WATER & SOAP.



INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF NECESSARY. INGESTION: DON'T INDUCE VOMITING. KEEP PERSON WARM & QUIET. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point:105F

Lower Limits:0.9%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL, OR WATER FOG.

Fire Fighting Procedures:TREAT AS A VOLATILE LIQUID FIRE. WATER SPRAY MAY BE INEFFECTIVE. IF WATER SPRAY IS USED, FOG NOZZLES ARE PREFERABLE.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. CONTAIN SPILL, ABSORB W/CLAY, SAND OR FLOOR ABSORBENT.

Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS & OPEN FLAMES. FOR STORAGE CONDITIONS SEE OSHA 1910.106. DON'T TAKE INTERNALLY. GROUND CONTAINERS WHEN POURING.

Other Precautions:AVOID CONTACT W/SKIN. AVOID FREE FALL OF >2-3 INCHES WHEN POURING.

Exposure Controls

Respiratory Protection:USE A NIOSH/MSHA JOINTLY APPROVED AIR SUPPLIED RESPIRATOR IF >TLV. USE AN APPROVED MECHANICAL FILTER TO REMOVE SOILD AIRBORNE PARTICLES OF OVERSPRAY DURING APPLICATION.

Ventilation:PROVIDE SUFFICIENT MECHANICAL (GENERAL &/OR LOCAL EXHAUST) TO KEEP Protective Gloves:RECOMMENDED

Eye Protection:SAFETY EYEWEAR

Other Protective Equipment:IMPERVIOUS CLOTHING & BOOTS.

Work Hygienic Practices:WASH HANDS BEFORE EATING, SMOKING OR USING BATHROOM. DON'T REUSE CONTAMINATED CLOTHING.

Supplemental Safety and Health

BOILING RANGE: 300-380

Chemical Properties

Boiling Pt:B.P. Text:SEE SUPP

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, OPEN FIRE, SPARKS, OPEN FLAME OR OTHER SOURCES OF IGNITION.

Disposal

Waste Disposal Methods:CONTAMINATED ABSORBENT MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. PREVENT RUN-OFF TO SEWERS, STREAMS OR OTHER BODIES OF WATER.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.