

FREMONT B-250 Boiler Water Treatment

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 02/01/2015

Supersedes: 02/08/2005

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : FREMONT B-250 Boiler Water Treatment
Product form : Mixture
Other means of identification : Base

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Boiler Water Treatment

1.3. Details of the supplier of the safety data sheet

FREMONT INDUSTRIES, INC.
4400 Valley Industrial Blvd. N.
P.O. Box 67
Shakopee, MN 55379-0067

1.4. Emergency telephone number

Emergency number : (952) 445-4121
CHEMTREC: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Corr. 1A H314

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS05

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) :

P260 - Do not breathe vapours, mist, fume
P264 - Wash hands, forearms and face thoroughly after handling
P280 - Wear eye protection, protective gloves
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a doctor, a POISON CENTER
P321 - Specific treatment (see Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work on this label)
P363 - Wash contaminated clothing before reuse
P405 - Store locked up
P501 - Dispose of contents/container to a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

FREMONT B-250 Boiler Water Treatment

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%
Sodium hydroxide	(CAS No) 1310-73-2	15 - 40

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If exposed or concerned, get medical attention/advice. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before re-use. Never give anything to an unconscious person.
- First-aid measures after inhalation : IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if breathing is affected. If breathing is difficult, supply oxygen.
- First-aid measures after skin contact : IN ON SKIN (or clothing): Remove affected clothing and wash all exposed skin with water for at least 15 minutes. Get medical attention immediately.
- First-aid measures after eye contact : IF IN EYES: Immediately flush with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do so. Get medical attention immediately. Continue rinsing.
- First-aid measures after ingestion : IF SWALLOWED: rinse mouth thoroughly. Do not induce vomiting without advice from poison control center or medical professional. Get medical attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Causes severe skin burns and eye damage.
- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : Highly corrosive to skin.
- Symptoms/injuries after eye contact : Causes serious eye damage.
- Symptoms/injuries after ingestion : May cause gastrointestinal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Foam. Dry powder. Sand. Water spray.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : The product is not flammable.
- Explosion hazard : Product is not explosive.
- Reactivity : Contact with reactive metals (e.g. aluminum) may result in the generation of hydrogen gas.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not dispose of fire-fighting water in the environment. Prevent human exposure to fire, fumes, smoke and products of combustion.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Evacuate area. Keep upwind. Ventilate area. Spill should be handled by trained clean-up crews properly equipped with respiratory equipment and full chemical protective gear (see Section 8).

6.1.1. For non-emergency personnel

- Protective equipment : Wear Protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Wear suitable protective clothing, gloves and eye or face protection. Approved supplied-air respirator, in case of emergency.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Sweep or shovel spills into appropriate container for disposal.

FREMONT B-250 Boiler Water Treatment

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Methods for cleaning up

: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Product may create slip hazard. Wash spill area thoroughly with plenty of soap and water. If slipperiness remains, apply additional dry-sweeping compound. Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Wear recommended personal protective equipment. Ensure good ventilation of the work station. Do not breathe vapours, mist. Avoid spilling the product, as this might cause danger of slippage and falls. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in dry, well-ventilated area. Keep container closed when not in use.

Incompatible materials

: Strong bases.

Storage temperature

: room temperature

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Sodium hydroxide (1310-73-2)	
ACGIH Ceiling (mg/m ³)	2
OSHA PEL (TWA) (mg/m ³)	2
OSHA PEL (Ceiling) (mg/m ³)	2

8.2. Exposure controls

Appropriate engineering controls

: Provide adequate general and local exhaust ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Use explosion-proof equipment with flammable materials. Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

: Gloves. Wear chemical goggles and face shield in combination. Protective clothing.



Hand protection

: Use gloves chemically resistant to this material when prolonged or repeated contact could occur. Gloves should be classified under Standard EN 374 or ASTM F1296. Suggested glove materials are: Neoprene, Nitrile/butadiene rubber, Polyethylene, Ethyl vinyl alcohol laminate, PVC or vinyl. Change contaminated gloves immediately. Suitable gloves for this specific application can be recommended by the glove supplier.

Eye protection

: Wear eye protection, including chemical splash goggles and a face shield when possibility exists for eye contact due to spraying liquid or airborne particles. Chemical goggles and face shield must be worn in combination.

Skin and body protection

: Wear long sleeves, and chemically impervious PPE/coveralls to minimize bodily exposure.

Respiratory protection

: Use NIOSH-approved dust/particulate respirator. Where vapor, mist, or dust exceed PELs or other applicable OELs, use NIOSH-approved respiratory protective equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

: Liquid

Color

: Colorless to slightly colored.

Odor

: No data available

Odor Threshold

: No data available

pH

: No data available

Relative evaporation rate (butylacetate=1)

: No data available

Melting point

: 145 °C (293 °F)

Freezing point

: No data available

Boiling point

: No data available

Flash point

: No data available

Auto-ignition temperature

: No data available

FREMONT B-250 Boiler Water Treatment

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 6.3 mm Hg
Relative vapour density at 20 °C	: No data available
Relative density	: 1.28 (H ₂ O = 1)
Solubility	: Water: 100 %
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Contact with reactive metals (e.g. aluminum) may result in the generation of hydrogen gas.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids. Strong oxidizing agents. Flammable liquids. Halogenated compounds. nitro-organic compounds.

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Sodium hydroxide (1310-73-2)

LD50 dermal rabbit	1350 mg/kg
--------------------	------------

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
---------------------------	--

Serious eye damage/irritation	: Not classified
-------------------------------	------------------

Respiratory or skin sensitisation	: Not classified
-----------------------------------	------------------

Germ cell mutagenicity	: Not classified
------------------------	------------------

Carcinogenicity	: Not classified
-----------------	------------------

Reproductive toxicity	: Not classified
-----------------------	------------------

Specific target organ toxicity (single exposure)	: Not classified
--	------------------

Specific target organ toxicity (repeated exposure)	: Not classified
--	------------------

Aspiration hazard	: Not classified
-------------------	------------------

Symptoms/injuries after inhalation	: May cause respiratory irritation.
------------------------------------	-------------------------------------

Symptoms/injuries after skin contact	: Highly corrosive to skin.
--------------------------------------	-----------------------------

Symptoms/injuries after eye contact	: Causes serious eye damage.
-------------------------------------	------------------------------

Symptoms/injuries after ingestion	: May cause gastrointestinal irritation.
-----------------------------------	--

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No information available.

12.2. Persistence and degradability

FREMONT B-250 Boiler Water Treatment

Persistence and degradability	No information available.
-------------------------------	---------------------------

FREMONT B-250 Boiler Water Treatment

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Do not discharge to public wastewater systems without permit of pollution control authorities.
No discharge to surface waters is allowed without an NPDES permit.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1824, SODIUM HYDROXIDE SOLUTION, 8, PGII

UN-No.(DOT) : 1824

DOT NA no. : UN1824

Proper Shipping Name (DOT) : Sodium hydroxide solution

Department of Transportation (DOT) Hazard Classes : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : II - Medium Danger

DOT Quantity Limitations Passenger aircraft/rail : 1 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L
CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 52 - Stow "separated from" acids

Additional information

Other information : No supplementary information available.

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

FREMONT B-250 Boiler Water Treatment

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

SARA Section 311/312 Hazard Classes : Immediate (acute) health hazard

Sodium hydroxide (1310-73-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

RQ (Reportable quantity, section 304 of EPA's : 1000 lb
List of Lists) :

15.2. International regulations

CANADA

No additional information available.

15.3. US State regulations

California Proposition 65

This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

Sodium hydroxide (1310-73-2)

U.S. - Massachusetts - Right To Know List

FREMONT B-250 Boiler Water Treatment

Safety Data Sheet

Prepared according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium hydroxide (1310-73-2)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Indication of changes : Revision 1.0: New SDS Created.


Revision date : 01/29/2015

Other information : Author: BCS.

NFPA health hazard : 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



HMIS III Rating

Health : 3

Flammability : 0

Physical : 1

Personal Protection :

FREMONT'S PRODUCTS ARE SOLD "AS IS." FREMONT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WITH RESPECT TO ITS PRODUCTS OR RELATED SERVICES. ALL SUCH EXPRESS AND IMPLIED WARRANTIES, INCLUDING BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE SPECIFICALLY DISCLAIMED.