

SPRAYPAK CHEWING GUM & CANDLE WAX REMOVER

1. Product And Company Identification

Supplier

Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA

Company Contact: Aludia B. Hernandez **Telephone Number:** 708-865-1000

FAX Number: 708-865-0923 **E-Mail:** sales@chaseproducts.com **Web Site:** www.chaseproducts.com

Supplier Emergency Contacts & Phone Number

Chem-Tel: 1-800-255-3924

Manufacturer

Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA

Company Contact: Aludia B. Hernandez **Telephone Number:** 708-865-1000

FAX Number: 708-865-0923 **E-Mail:** sales@chaseproducts.com **Web Site:** www.chaseproducts.com

Manufacturer Emergency Contacts & Phone Number

Chem-Tel: 1-800-255-3924

Issue Date: 09/15/2008

Product Name: SPRAYPAK CHEWING GUM & CANDLE WAX REMOVER

Chemical Name: 5-5615 CAS Number: Not Established

MSDS Number: 4335 Product Code: 433-4107-3

<u>Product/Material Uses</u> - Chewing Gum Remover

2. Composition/Information On Ingredients

Ingredient	CAS	Percent Of
Name	Number	Total Weight
ISOBUTANE	75-28-5	
PROPANE	74-98-6	

3. Hazards Identification

<u>Primary Routes(s) Of Entry</u> - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation.

Eye Hazards - Can cause severe eye irritation, redness, tearing and possible freeze burns.

Skin Hazards - Prolonged contact with the skin may cause severe freeze burns.

Ingestion Hazards - This is an aerosol product, ingestion is unlikely to occur.

Inhalation Hazards - Over inhalation of vapor or mist may produce anesthetic effects, headache and dizziness.

<u>Chronic/Carcinogenicity Effects</u> - Not known, chronic effects based on available data. None of the ingredients on this product are listed as carcinogenic by NTP, IARC or OSHA

Teratogenicity (Birth Defects) - Not known

Reproductive Effects - Not known

Neurotoxicity - Not known

Mutagenicity (Genetic Effect) - Not known

<u>Signs And Symptoms</u> - Acute: Over inhalation of vapor or mist may cause anesthetic effects, headaches, dizziness and nausea. Prolonged contact with skin may cause severe freeze burns. Can cause severe eye irritation, redness, tearing and possible freeze burns.

Conditions Aggravated By Exposure - May aggravate pre-existing skin and respiratory disorders.

Conditions Aggravated By Overexposure - May aggravate pre-existing skin and respiratory disorders.

SPRAYPAK CHEWING GUM & CANDLE WAX REMOVER

First Aid (Pictograms)





4. First Aid Measures

Eye - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

Skin - Wash skin with soap and water. Consult physician if injury develops.

Ingestion - Ingestion from an aerosol product is unlikely to occur.

<u>Inhalation</u> - If overcome by vapor move person to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.

5. Fire Fighting Measures

Flash Point: -156 °F

Flash Point Method: estimated

Lower Explosive Limit: 1.9% (vol) gas in air **Upper Explosive Limit:** 9.5% (vol) gas in air

<u>Fire And Explosion Hazards</u> - Vapors are havier than air and may travel along the ground and be ignite by pilot lights, other flames, sparks, heaters, smoking or other ignition sources.

Extinguishing Media - Dry chemical extinguisher (B-C), water.

<u>Fire Fighting Instructions</u> - Stop the release of material if possible. Water spray may be used to cool cans in the vicinity of fire or excessive heat. Remove personnel in general area.

6. Accidental Release Measures

Provide adequate ventilation to area being treated. Avoid sources of ignition.

Handling & Storage (Pictograms)



7. Handling And Storage

Handling And Storage Precautions - Store in a cool, dry place away from heat and open flame.

<u>Handling Precautions</u> - Do not deliberately inhale vapor or spray mist. Avoid getting spray into eyes. Avoid contact with skin. Keep out of reach of children.

<u>Storage Precautions</u> - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity). **AEROSOL STORAGE LEVEL III (NFPA-30B)**

Work/Hygienic Practices - Wash thoroughly after handling.

Protective Clothing (Pictograms)





SPRAYPAK CHEWING GUM & CANDLE WAX REMOVER

8. Exposure Controls/Personal Protection

Engineering Controls - Use with adequate general and local exhaust ventilation.

Eye/Face Protection - Conventional eyeglasses to guard against splashing.

Skin Protection - Household type gloves, required.

<u>Respiratory Protection</u> - Use in well-ventilated area ONLY. When using indoors, keep windows and doors open until fumes disipate.

Ingredient(s) - Exposure Limits

PROPANE

ACGIH TLV-TWA 2500 ppm; OSHA PEL-TWA 1,000 ppm

9. Physical And Chemical Properties

<u>Appearance</u> - Not visible vapor.<u>Odor</u> - Sweet, petroleum odor.

Chemical Type: Mixture **Physical State:** Gas

Melting Point: Not applicable °F Not applicable °C

Boiling Point: -6.4 to 10.9 °F Specific Gravity: 0.555 Percent VOCs: 100 Vapor Pressure: 46psig Solubility: 0.008%

Evaporation Rate: Immediate

10. Stability And Reactivity

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions To Avoid (Stability) - Temperatures above 120 F

Incompatible Materials - Avoid heat and open flame.

Hazardous Decomposition Products - Thermal decomposition may yield gases like carbon monoxide and carbon

dioxide.

Conditions To Avoid (Polymerization) - Temperatures above 120 F

11. Toxicological Information

No Data Available...

12. Ecological Information

No Data Available...

13. Disposal Considerations

Mechanical recovery. Flare-off at safe locations (vapors). Exhaust to atmosphere in safe location (no open flames). Do not puncture or incinerate container. **If empty:** Place in trash or offer for recycling if available. **If partly filled:** Call your local solid waste agency for disposal instructions.

14. Transport Information

<u>Proper Shipping Name</u> - ORM-D Consumer Commodity

SPRAYPAK CHEWING GUM & CANDLE WAX REMOVER

14. Transport Information - Continued

Hazard Class

2.1

DOT Identification Number

UN1950

DOT Shipping Label

Aerosol Consumer Commodity

15. Regulatory Information

<u>U.S. Regulatory Information</u> - All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard

<u>SARA Section 313 Notification</u> - This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

Ingredient(s) - State Regulations

ISOBUTANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

PROPANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

NFPA 1 NA

HMIS HEALTH 1 FLAMMABILITY 4 REACTIVITY 1 PERSONAL PROTECTION B

16. Other Information

Revision/Preparer Information

MSDS Preparer: Laura E. Radevski

MSDS Preparer Phone Number: 708-865-1000

This MSDS Supersedes A Previous MSDS Dated: 03/18/2005

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

MATERIAL SAFETY DATA SHEET SPRAYPAK CHEWING GUM & CANDLE WAX REMOVER

Disclaimer - Continued	
Chase Products Co.	

Printed Using MSDS Generator™ 2000